



Mortise lock for metal frame doors, prepared for profile cylinder, zinc plated lock case, solid follower, with action of the key on the latch bolt, **2 turn**, top and bottom of lock case closed. Certified as per EN 12209.

| 1448 | | | | | Standard designs and special designs | |
|---|----|----|----|----|---|-----------|
| Backset in mm | 30 | 35 | 40 | 45 | Forend 16, 20 or 22 mm | * |
| Widths in mm | 45 | 50 | 55 | 60 | U-shaped forend 22 or 24 mm | * |
| Dead bolt throw 25 mm | | | ■ | | Controlled latch bolt stop (FS approval not applicable) | * |
| Follower in mm | 8 | 9 | * | 10 | Prepared for RZ 22 (swiss standard) | * |
| Reversible latch bolt | | | ■ | | Dead bolt monitoring device including 10m cable | * |
| Latch bolt extended 3 or 5 mm | | | * | | Follower monitoring device including 8 m cable | * |
| Dead bolt extended 3 or 5 mm | | | * | | Refurbishment forend 380 mm | * |
| Forend steel zinc plated | | | * | | Fire doors | * |
| Forend stainless steel Latch and dead bolt nickel-plated | | | ■ | | For burglar resistance doors according to EN 1627 RC2 | * |
| Forend 24 mm | | | ■ | | Matching striking plates on page | 201 - 203 |

■ Standard design □ Special design

* On request